

Aluminum Sulfate 16 Hydrate

Safety Data Sheet

IDENTIFICATION

Product Identifier

Product Name Aluminum Sulfate 16 Hydrate

Supplier

Shri Shanti Laboratories
Shri Shanti Niwas, Gangashahar Road,
Bikaner, India-334001

Other means of identification

Synonyms ALUM.

Recommended use of the chemical and restrictions on use

Recommended Use Water treatment coagulant, flocculent, alumina source for catalyst, pH control in papermaking/water treatment.

Emergency Telephone Number

Company Phone Number +91-9571511119

Emergency Telephone (24 hr) +91-9799144441

2. HAZARDS IDENTIFICATION

Appearance Colorless to clear amber or clear light green liquid

Physical State Liquid

Odor Negligible

Classification

Irritating to eyes	Category 2
Corrosive to Metals	Category 1

Signal Word

Warning

Hazard Statements

May be harmful if swallowed
Causes eye irritation
May be corrosive to metals



Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
Wear protective gloves, and eye protection. Keep only in original container

Precautionary Statements - Response

If swallowed: Call a poison center or doctor if you feel unwell. Rinse mouth.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical attention.

Precautionary Statements - Storage

Store in corrosive resistant container or container with a resistant inner liner

Precautionary Statements - Disposal

Dispose in accordance with all applicable regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262. Hazardous Waste Number(s): May be D002 under §261.22(a)(2) due to the rate of corrosion of metal.

Aluminum Sulfate 16 Hydrate

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms ALUM.
Chemical Family Inorganic Salt.

Chemical Name	CAS No	Weight-%
Water	7732-18-5	>50
Aluminum Sulfate	16828-11-8	<50

4. FIRST-AID MEASURES

First Aid Measures

Eye Contact If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor/physician if irritation continues.

Skin Contact Flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical aid if irritation develops or persists. Wash clothing before reuse.

Inhalation If adverse effects occur, remove to fresh air and observe. If not breathing, give artificial respiration. Seek immediate medical attention/advice.

Ingestion If a large amount is swallowed, get medical attention immediately.

Most important Causes serious eye damage. May cause skin irritation. **symptoms and effects**

Symptoms

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Aluminum Sulfate will not burn. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Small Fire Move containers from fire area if you can do it without risk. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas.

Large Fire Same procedures as for small fires.

Specific Hazards Arising from the Chemical

Negligible fire hazard.

Hazardous Decomposition Products Oxides of sulfur.

Sensitivity to Mechanical Impact Not sensitive.

Sensitivity to Static Discharge Not sensitive.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Do not release runoff from fire control methods to sewers or waterways.

Aluminum Sulfate 16Hydrate

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions	Use personal protection recommended in Section 8. Keep unnecessary people away, isolate hazard area and deny entry.
Environmental Precautions	Do not release into sewers or waterways. For spills in excess of allowable limits (RQ) notify the National Response Center (800) 424-8802; refer to SARA Title III, Section 313 40 CFR 372, and CERCLA 40 CFR 302 for detailed instructions concerning reporting requirements. Notify Local Emergency Planning Committee (LEPC) and State Emergency Response Commission (SERC) for a release greater than or equal to Reportable Quantities (RQ). Refer to U.S. SARA Section 304. See Section 12 for additional Ecological Information.

Methods and material for containment and clean up

Methods for Containment	Prevent further leakage or spillage if safe to do so.
Methods for Clean-Up	Small Spills: Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling	Avoid contact with skin, eyes or clothing. Handle in accordance with good industrial hygiene and safety practice. Wash face, hands and any exposed skin thoroughly after handling. Store and handle in accordance with all current regulations and standards.
--------------------------------	---

Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep container tightly closed and store in a cool, dry and well-ventilated place. Store with acids. See original container for storage recommendations. Store away from incompatible materials.
Incompatible Materials	Alkalis, metals. Alkalis (bases): Violent reaction. Metals: May be corrosive in the presence of moisture.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

<u>Exposure Guidelines</u>	No exposure limits noted for product. Exposure Limits for aluminum metal NIOSH REL - TWA 10 mg/m ³ (total) TWA 5 mg/m ³ (resp) OSHA PEL - TWA 15 mg/m ³ (total) TWA 5 mg/m ³ (resp)
-----------------------------------	--

Appropriate engineering controls

Engineering Controls	Apply technical measures to comply with the occupational exposure limits. Ensure adequate ventilation, especially in confined areas. Maintain eye wash fountain and quick-drench facilities in work area.
-----------------------------	---

Individual protection measures, such as personal protective equipment

Eye/Face Protection	Wear chemical tight goggles and full face shield.
Skin and Body Protection	Wear appropriate chemical resistant clothing including chemical resistant gloves.

Aluminum Sulfate 16Hydrate

Respiratory Protection

Seek professional advice prior to respirator selection and use. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen.
WARNING!: Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Colorless to clear amber or clear light green liquid
Odor	Negligible
Odor threshold	Not determined
pH	2.0-2.4
Relative density; (specific gravity)	±1.3 @15.5 °C
Melting point/freezing point	-13° C / 9° F
Initial boiling point and boiling range	Not relevant
Decomposition temperature	±1,400° F
Viscosity	5-25 centipoise
Auto-ignition temperature	Not flammable
Evaporation rate;	Similar to water
Flammability (solid, gas)	Not flammable
Flash point	Will not burn
Upper/lower flammability or explosive limits	Will not burn
Partition coefficient: n-octanol/water	Not relevant
Solubility	Soluble in water
Vapor density	Similar to water
Vapor pressure	Similar to water

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to Avoid

Protect from freezing. Keep separated from incompatible substances.

Incompatible Materials

Alkalis, metals. Alkalis (bases): Violent reaction. Metals: May be corrosive in the presence of moisture.

Hazardous Decomposition Products

Thermal oxidative decomposition of Aluminum Sulfate occurs at temperatures greater than 1400°F and can produce sulfur oxides.

Aluminum Sulfate 16Hydrate

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye Contact	Causes serious eye damage.
Skin Contact	May cause skin irritation.
Inhalation	Avoid breathing vapors or mists.
Ingestion	Do not taste or swallow. May be harmful if swallowed.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Aluminum Sulfate 16828-11-8	= 1930 mg/kg (Rat)	-	-

Information on physical, chemical and toxicological effects

Symptoms	Please see section 4 of this SDS for symptoms.
-----------------	--

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity	This product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.
------------------------	--

Numerical measures of toxicity

Not determined

12. ECOLOGICAL INFORMATION

Ecotoxicity

Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Aluminum Sulfate 16828-11-8		100: 96 h Carassius auratus mg/L LC50 37: 96 h Gambusia affinis mg/L LC50 static		136: 15 min Daphnia magna mg/L EC50

Persistence/Degradability

Not determined

Bioaccumulation

Not determined

Mobility

Not determined

Other Adverse Effects

Not determined

Aluminum Sulfate 16 Hydrate

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and regulations.

US EPA Waste Number

EPA Hazardous Waste Code: D002 (Corrosive) if the pH is <2. May be D002 per 40CFR261.22(a)(2) due to the rate of corrosion of steel. The U.S. EPA has not published waste codes for this products components.

14. TRANSPORT INFORMATION

Note

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances. Information also applies to TDG, ADR and RID.

DOT

UN/ID No NA
Proper Shipping Name NA
Hazard Class NA
Packing Group NA
Reportable Quantity (RQ) NA

IATA

UN/ID No NA
Proper Shipping Name NA
Hazard Class NA
Packing Group NA

IMDG

UN/ID No NA
Proper Shipping Name NA
Hazard Class NA
Packing Group NA

15. REGULATORY INFORMATION

International Inventories

Not determined

US Federal Regulations

CERCLA

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Aluminum Sulfate 16828-11-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

SARA 311/312 Hazard Categories

Acute Health Hazard Yes
Chronic Health Hazard No

Aluminum Sulfate 16 Hydrate

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

CWA (Clean Water Act)

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Aluminum Sulfate 16828-11-8 (<50)	5000 lb			X

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Aluminum Sulfate 16828-11-8	X	X	X

16. OTHER INFORMATION

	Health Hazards	Flammability	Instability	Special Hazards
NFPA	1	0	0	Not determined

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data
Sheet